Index

IEE Proceedings-B
Electric Power Applications
Vol. 138, 1991

ABBREVIATIONS

- p paper, address or lecture
- d discussion on a paper
- a abstract of paper or address
- e errata

Author index

A

Abdel-Halim, M.A., and Manning, C.D. Modelling a laminated brushless exciter-alternator unit in all modes of operation p87
Al-Aubidy, K.M., Binns, K.J., and Shimmin, D.W. see Binns, K.J.
Al-Taee, M.A., Mellor, P.H., and Binns, K.J. see Mellor, P.H.
Al Zahawi, B.A.T., Jones, B.L., and Drury, W. Electrical characteristics of alternative recovery convertors for slip-energy recovery drives p193
Allan, J., Brown, J.C., and Mellitt, B. see Brown, J.C.
Arrillaga, J., and Villablanca, M.E. Pulse doubling in parallel convertor configurations with interphase reactors p15

B

Barnes, R., and Wong, K.T. Unbalance and harmonic studies for the Channel Tunnel railway system p41
Binns, K.J., Mellor, P.H., and Al-Taee, M.A. see Mellor, P.H.
Binns, K.J., Mellor, P.H., and Chaaban, F.B. see Mellor, P.H.
Binns, K.J., Shimmin, D.W., and Al-Aubidy, K.M. Implicit rotor-position sensing using motor windings for a self-commutating permanent-magnet drive system p28
Binns, K.J., Turner, D.R., Shamsadeen, B.N., and Warne, D.F. see Turner, D.R.
Bouillault, F., Lemaire-Semail, B., and Razek, A. see Lemaire-Semail, B.
Brown, J.C., Allan, J., and Mellitt, B. Six-pulse three-phase rectifier bridge models for calculating closeup and remote short circuit transients on DC supplied railways p303

C

Carpenter, D.C., and Hill, R.J. see Hill, R.J.
Chaaban, F.B., Mellor, P.H., and Binns, K.J. see Mellor, P.H.
Chen, T.H., Liaw, C.M., Wang, T.C., Cho, G.J., Lee, C.M., and Wang, C.T. see Liaw, C.M.
Cheng, K.W.E., and Evans, P.D. Parallel-mode extended-period quasiresonant convertor p243
Chew, W.M., and Evans, P.D. see Evans, P.D.
Chibani, A., and Nakaoka, M. Novel PWM-based control strategy of HF link SMR with sinusoidal line current p219
Cho, G.H., Chung, Y.H., and Shin, B.S. see Chung, Y.H.
Cho, G.J., Liaw, C.M., Chen, T.H., Wang, T.C., Lee, C.M., and Wang, C.T. see Liaw, C.M.
Chung, Y.H., Shin, B.S., and Cho, G.H. Bilateral series resonant inverter for high frequency link UPS p159
Cornick, K.J., and Tleis, A.N.D. Computer simulation of three-phase prestriking transients in cable-connected motor systems p105

D

Drury, W., Al Zahawi, B.A.T., and Jones, B.L. see Al Zahawi, B.A.T.

E

Evans, P.D., and Cheng, K.W.E. see Cheng, K.W.E.
Evans, P.D., and Chew, W.M. Reduction of proximity losses in coupled inductors p51

F

Fukushima, T., and Funabiki, S. see Funabiki, S.
Funabiki, S., and Fukushima, T. Current commands for high-efficiency torque control of DC shunt motor p227

G

Gieras, J.F. Analysis of multilayer rotor induction motor with higher space harmonics taken into account p59
Green, T.C., and Williams, B.W. see Williams, B.W.

H

Hamada, S., Ogino, Y., and Nakaoka, M. Saturable reactor assisted soft-switching full-bridge DC–DC power convertors p95
Hill, R.J., and Carpenter, D.C. Determination of rail internal impedance for electric railway traction system simulation p311
Ho, S.C., Hong, C.G., and Hwang, G.J. see Hong, C.G.
Hong, C.-G., and Hwang, G.-J. Nonlinear complex finite-element analysis of squirrel cage induction motor performance p277
Hong, C.G., Ho, S.C., and Hwang, G.J. Characteristics of a squirrel cage induction motor p115
Hwang, G.-J., and Hong, C.-G. see Hong, C.-G.
Hwang, G.J., Hong, C.G., and Ho, S.C. see Hong, C.G.

I

Ishikawa, T., and Kataoka, T. V curve of hysteresis motor p137
Ishizaka, K., and Itoh, R. see Itoh, R.
Itoh, R., and Ishizaka, K. Single-phase sinusoidal rectifier with step-up/down characteristics p338
Itoh, R., and Ishizaka, K. Three-phase flyback AC-DC convertor with sinusoidal supply currents p143

J

Jiang, C.G., and Sun, S.Q. see Sun, S.Q.
Jones, B.L., Al Zahawi, B.A.T., and Drury, W. see Al Zahawi, B.A.T.

K

Karunadasa, J.P., and Renfrew, A.C. Design and implementation of microprocessor based sliding mode controller for brushless servomotor p345
Kataoka, T., and Ishikawa, T. see Ishikawa, T.
Kazimierczuk, M.K. Class D voltage-switching MOSFET power amplifier p285
Kiyokawa, H., and Sun, S.Q. see Sun, S.Q.
Kwon, B.H., and Song, E.H. Design of current source using 12-pulse phase-controlled rectifier p185

L

Lang, J.H., and Torrey, D.A. see Torrey, D.A.
Lee, C.M., Liaw, C.M., Chen, T.H., Wang, T.C., Cho, G.J., and Wang, C.T. see Liaw, C.M.
Lemaire-Semail, B., Bouillault, F., and Razek, A. Modelling of vector controlled cage induction motor with FEM p297
Liaw, C.M., Chen, T.H., Wang, T.C., Cho, G.J., Lee, C.M., and Wang, C.T. Design and implementation of a single phase current-forced switching mode bilateral convertor p129

M

Manias, S. Novel full bridge semicontrolled switch mode rectifier p252
Manning, C.D., and Abdel-Halim, M.A. see Abdel-Halim, M.A.
Mellitt, B., Brown, J.C., and Allan, J. see Brown, J.C.
Mellor, P.H., Al-Taee, M.A., and Binns, K.J. Open loop stability characteristics of synchronous drive incorporating high field permanent magnet motor p175
Mellor, P.H., Chaaban, F.B., and Binns, K.J. Estimation of parameters and performance of rare-earth permanent-magnet motors avoiding measurement of load angle p322
Mellor, P.H., Roberts, D., and Turner, D.R. Lumped parameter thermal model for electrical machines of TEFC design p205
Mukherjee, P.K., Sarkar, D., and Sen, S.K. see Sarkar, D.

N

Nakaoka, M., Hamada, S., and Ogino, Y. see Hamada, S.
Nakaoka, M., and Chibani, A. see Chibani, A.

O

Ogino, Y., Hamada, S., and Nakaoka, M. see Hamada, S.

P

Pulle, D.W.J. New data base for switched reluctance drive simulation p331

R

Razek, A., Lemaire-Semail, B., and Bouillault, F. see Lemaire-Semail, B.
Renfrew, A.C., and Karunadasa, J.P. see Karunadasa, J.P.
Roberts, D., Mellor, P.H., and Turner, D.R. see Mellor, P.H.
Robinson, M.J., and Williamson, S. see Williamson, S.

S

Sarkar, D., Mukherjee, P.K., and Sen, S.K. Use of 3-dimensional finite elements for computation of temperature distribution in the stator of an induction motor p75
Sen, S.K., Sarkar, D., and Mukherjee, P.K. see Sarkar, D.
Shamsadeen, B.N., Turner, D.R., Binns, K.J., and Warne, D.F. see Turner, D.R.
Shimmin, D.W., Binns, K.J., and Al-Aubidy, K.M. see Binns, K.J.
Shin, B.S., Chung, Y.H., and Cho, G.H. see Chung, Y.H.
Song, E.H., and Kwon, B.H. see Kwon, B.H.
Spooner, E., and Zuncheng, Z. see Zuncheng, Z.
Sun, S.Q., and Jiang, C.G. Decomposition of Czarnecki's reactive current and reactive power p125
Sun, S.Q., and Kiyokawa, H. Decomposition of voltage, current and power p35

T

Tleis, A.N.D., and Cornick, K.J. see Cornick, K.J.
Torrey, D.A., and Lang, J.H. Optimal-efficiency excitation of variable-reluctance motor drives p1
Tozune, A. Balanced operation of three-phase induction motor with asymmetrical stator windings connected to single-phase supply system p167
Tozune, A. Vibration characteristics of motors with dynamic absorbers p21
Turner, D.R., Binns, K.J., Shamsadeen, B.N., and Warne, D.F. Accurate measurement of induction motor losses using balance calorimeter p233
Turner, D.R., Mellor, P.H., and Roberts, D. see Mellor, P.H.

V

Villablanca, M.E., and Arrillaga, J. see Arrillaga, J.

W

Wang, C.T., Liaw, C.M., Chen, T.H., Wang, T.C., Cho, G.J., and Lee, C.M. see Liaw, C.M.

Wang, T.C., Liaw, C.M., Chen, T.H., Cho, G.J., Lee, C.M., and Wang, C.T. see Liaw, C.M.

Warne, D.F., Turner, D.R., Binns, K.J., and Shamsadeen, B.N. see Turner, D.R.

Williams, B.W., and Green, T.C. Steady-state control of an induction motor by estimation of stator flux magnitude p69

Williamson, S., and Robinson, M.J. Calculation of cage induction motor equivalent circuit parameters using finite elements p264

Wong, K.T., and Barnes, R. see Barnes, R.

Wouterse, J.H. Critical torque and speed of eddy current brake with widely separated soft iron poles p153

Z

Zuncheng, Z., and Spooner, E. High-speed reluctance machines with mixed-pole windings p257

AMPLIFIERS

Class D voltage-switching MOSFET power amplifier. M.K. Kazimierczuk p285

COMMUTATION

Implicit rotor-position sensing using motor windings for a self-commutating permanent-magnet drive system. K.J. Binns, D.W. Shimmin and K.M. Al-Aubidy p28

COMPUTER APPLICATIONS

Six-pulse three-phase rectifier bridge models for calculating closeup and remote short circuit transients on DC supplied railways. J.C. Brown, J. Allan and B. Mellitt p303

COMPUTER SIMULATION

Computer simulation of three-phase prestriking transients in cable-connected motor systems. K.J. Cornick and A.N.D. Tleis p105

CONTROL SYSTEMS

Design and implementation of microprocessor based sliding mode controller for brushless servomotor. J.P. Karunadasa and A.C. Renfrew p345
Steady-state control of an induction motor by estimation of stator flux magnitude. B.W. Williams and T.C. Green p69

CONVERTORS

Design and implementation of a single phase current-forced switching mode bilateral convertor. C.M. Liaw, T.H. Chen, T.C. Wang, G.J. Cho, C.M. Lee and C.T. Wang p129
Design of current source using 12-pulse phase-controlled rectifier. B.H. Kwon and E.H. Song p185
Electrical characteristics of alternative recovery convertors for slip-energy recovery drives. B.A.T. Al Zahawi, B.L. Jones and W. Drury p193
Novel full bridge semicontrolled switch mode rectifier. S. Manias p252
Parallel-mode extended-period quasiresonant convertor. K.W.E. Cheng and P.D. Evans p243
Pulse doubling in parallel convertor configurations with interphase reactors. J. Arrillaga and M.E. Villablanca p15
Reduction of proximity losses in coupled inductors. P.D. Evans and W.M. Chew p51
Saturable reactor assisted soft-switching full-bridge DC–DC power convertors. S. Hamada, Y. Ogino and M. Nakaoka p95
Single-phase sinusoidal rectifier with step-up/down characteristics. R. Itoh and K. Ishizaka p338
Three-phase flyback AC-DC convertor with sinusoidal supply currents. R. Itoh and K. Ishizaka p143

EDDY CURRENTS

Critical torque and speed of eddy current brake with widely separated soft iron poles. J.H. Wouterse p153
Reduction of proximity losses in coupled inductors. P.D. Evans and W.M. Chew p51

ELECTROMAGNETIC THEORY

Analysis of multilayer rotor induction motor with higher space harmonics taken into account. J.F. Gieras p59

FEEDBACK

Steady-state control of an induction motor by estimation of stator flux magnitude. B.W. Williams and T.C. Green p69

HYSTERESIS

V curve of hysteresis motor. T. Ishikawa and T. Kataoka p137

INDUCTION MOTORS

Accurate measurement of induction motor losses using balance calorimeter. D.R. Turner, K.J. Binns, B.N. Shamsadeen and D.F. Warne p233
Analysis of multilayer rotor induction motor with higher space harmonics taken into account. J.F. Gieras p59
Balanced operation of three-phase induction motor with asymmetrical stator windings connected to single-phase supply system. A. Tozune p167
Calculation of cage induction motor equivalent circuit parameters using finite elements. S. Williamson and M.J. Robinson p264
Characteristics of a squirrel cage induction motor. C.G. Hong, S.C. Ho and G.J. Hwang p115
High-speed reluctance machines with mixed-pole windings. Z. Zuncheng and E. Spooner p257
Lumped parameter thermal model for electrical machines of TEFC design. P.H. Mellor, D. Roberts and D.R. Turner p205
Modelling of vector controlled cage induction motor with FEM. B. Lemaire-Semail, F. Bouillault and A. Razek p297
Nonlinear complex finite-element analysis of squirrel cage induction motor performance. C.-G. Hong and G.-J. Hwang p277
Steady-state control of an induction motor by estimation of stator flux magnitude. B.W. Williams and T.C. Green p69
Use of 3-dimensional finite elements for computation of temperature distribution in the stator of an induction motor. D. Sarkar, P.K. Mukherjee and S.K. Sen p75

INSTRUMENTATION AND MEASURING SCIENCE

Accurate measurement of induction motor losses using balance calorimeter. D.R. Turner, K.J. Binns, B.N. Shamsadeen and D.F. Warne p233

MAGNETIC DEVICES AND PROPERTIES

Current commands for high-efficiency torque control of DC shunt motor. S. Funabiki and T. Fukushima p227
Implicit rotor-position sensing using motor windings for a self-commutating permanent-magnet drive system. K.J. Binns, D.W. Shimmin and K.M. Al-Aubidy p28
Open loop stability characteristics of synchronous drive incorporating high field permanent magnet motor. P.H. Mellor, M.A. Al-Taee and K.J. Binns p175

MAGNETIC FIELDS

Characteristics of a squirrel cage induction motor. C.G. Hong, S.C. Ho and G.J. Hwang p115

MATHEMATICAL TECHNIQUES

Calculation of cage induction motor equivalent circuit parameters using finite elements. S. Williamson and M.J. Robinson p264
Characteristics of a squirrel cage induction motor. C.G. Hong, S.C. Ho and G.J. Hwang p115
Nonlinear complex finite-element analysis of squirrel cage induction motor performance. C.-G. Hong and G.-J. Hwang p277

MICROPROCESSORS

Design and implementation of microprocessor based sliding mode controller for brushless servomotor. J.P. Karunadasa and A.C. Renfrew p345

MOTORS

Computer simulation of three-phase prestriking transients in cable-connected motor systems. K.J. Cornick and A.N.D. Tleis p105
Critical torque and speed of eddy current brake with widely separated soft iron poles. J.H. Wouterse p153
Current commands for high-efficiency torque control of DC shunt motor. S. Funabiki and T. Fukushima p227
V curve of hysteresis motor. T. Ishikawa and T. Kataoka p137
Vibration characteristics of motors with dynamic absorbers. A. Tozune p21

OPTIMISATION

Optimal-efficiency excitation of variable-reluctance motor drives. D.A. Torrey and J.H. Lang p1

PHASING AND PHASE CONTROL

Balanced operation of three-phase induction motor with asymmetrical stator windings connected to single-phase supply system. A. Tozune p167

POWER ELECTRONICS

Bilateral series resonant inverter for high frequency link UPS. Y.H. Chung, B.S. Shin and G.H. Cho p159
Class D voltage-switching MOSFET power amplifier. M.K. Kazimierczuk p285
Decomposition of voltage, current and power. S.Q. Sun and H. Kiyokawa p35
Electrical characteristics of alternative recovery convertors for slip-energy recovery drives. B.A.T. Al Zahawi, B.L. Jones and W. Drury p193
Novel full bridge semicontrolled switch mode rectifier. S. Manias p252
Parallel-mode extended-period quasiresonant convertor. K.W.E. Cheng and P.D. Evans p243
Single-phase sinusoidal rectifier with step-up/down characteristics. R. Itoh and K. Ishizaka p338
Three-phase flyback AC-DC convertor with sinusoidal supply currents. R. Itoh and K. Ishizaka p143

POWER SYSTEMS AND PLANT

Decomposition of Czarnecki's reactive current and reactive power. S.Q. Sun and C.G. Jiang p125
Decomposition of voltage, current and power. S.Q. Sun and H. Kiyokawa p35

RAILWAY ELECTRIFICATION AND TRANSPORTATION

Determination of rail internal impedance for electric railway traction system simulation. R.J. Hill and D.C. Carpenter p311
Six-pulse three-phase rectifier bridge models for calculating closeup and remote short circuit transients on DC supplied railways. J.C. Brown, J. Allan and B. Mellitt p303
Unbalance and harmonic studies for the Channel Tunnel railway system. R. Barnes and K.T. Wong p41

RELUCTANCE MOTORS

High-speed reluctance machines with mixed-pole windings. Z. Zuncheng and E. Spooner p257
New data base for switched reluctance drive simulation. D.W.J. Pulle p331
Optimal-efficiency excitation of variable-reluctance motor drives. D.A. Torrey and J.H. Lang p1

SERVOMOTORS

Design and implementation of microprocessor based sliding mode controller for brushless servomotor. J.P. Karunadasa and A.C. Renfrew p345

SIMULATION

Design of current source using 12-pulse phase-controlled rectifier. B.H. Kwon and E.H. Song p185
Modelling a laminated brushless exciter-alternator unit in all modes of operation. M.A. Abdel-Halim and C.D. Manning p87
Modelling of vector controlled cage induction motor with FEM. B. Lemaire-Semail, F. Bouillault and A. Razek p297

STABILITY

Open loop stability characteristics of synchronous drive incorporating high field permanent magnet motor. P.H. Mellor, M.A. Al-Taee and K.J. Binns p175

STEPPING MOTORS

New data base for switched reluctance drive simulation. D.W.J. Pulle p331

SWITCHES AND SWITCHING THEORY

Design and implementation of a single phase current-forced switching mode bilateral convertor. C.M. Liaw, T.H. Chen, T.C. Wang, G.J. Cho, C.M. Lee and C.T. Wang p129

Novel PWM-based control strategy of HF link SMR with sinusoidal line current. A. Chibani and M. Nakaoka p219

Saturable reactor assisted soft-switching full-bridge DC–DC power convertors. S. Hamada, Y. Ogino and M. Nakaoka p95

SYNCHRONOUS MOTORS

Estimation of parameters and performance of rare-earth permanent-magnet motors avoiding measurement of load angle. P.H. Mellor, F.B. Chaaban and K.J. Binns p322

High-speed reluctance machines with mixed-pole windings. Z. Zuncheng and E. Spooner p257

Open loop stability characteristics of synchronous drive incorporating high field permanent magnet motor. P.H. Mellor, M.A. Al-Taee and K.J. Binns p175

THYRISTORS

Design of current source using 12-pulse phase-controlled rectifier. B.H. Kwon and E.H. Song p185

Three-phase flyback AC-DC convertor with sinusoidal supply currents. R. Itoh and K. Ishizaka p143

VIBRATION

Vibration characteristics of motors with dynamic absorbers. A. Tozune p21